

Équipements sous pression

Annexe - Données détaillées

PUMY-M200YKM

6 janvier 2026

	PUMY-M200YKM	8 cv
	Réfrigérant	R32
Compressor	Model	MVB53FPCMC
	PS [bar]	41.5
	V [L]	1.4
	PS*V [bar*L]	58.1
	Category	II
	Approval	applied (with TÜV Rheinland)
Accumulator	Model	ACM-M00140-750
	PS [bar]	23.0
	V [L]	9.4
	PS*V [bar*L]	216.2
	Category	III
	Approval	applied (with TÜV Rheinland)
4-way valve	Model	STF-H0435
	PS [bar]	42
	V [L]	0.25
	PS*V [bar*L]	10.5
	Category	0
Oil separator	Model	-
	PS [bar]	41.5
	V [L]	0.93
	PS*V [bar*L]	38.4
	Category	0
High pressure switch	Model	ACB-1UB24
	PS [bar]	45
	Category	IV
	Approval	TUV Rheinland and DIN approval
Header	Model	-
	PS [bar]	41.5
	DN [φ]	<25
	PS*DN	-
	Category	0
Heat exchanger	Model	-
	PS [bar]	41.5
	DN [φ]	<25
	PS*DN	-
	Category	0
Distributor	Model	-
	PS [bar]	41.5
	DN [φ]	<25
	PS*DN	-
	Category	0

	PUMY-M200YKM	8 cv
	Réfrigérant	R32
LEV(1)	Model	UKV-40D542
	PS [bar]	41.5
	DN [φ]	<25
	PS*DN	-
	Category	0
LEV(2)	Model	FAM-BD17ME
	PS [bar]	41.5
	DN [φ]	<25
	PS*DN	-
	Category	0
HIC	Model	-
	PS [bar]	41.5
	DN [φ]	<25
	PS*DN	-
	Category	0
Solenoid valve	Model	VPV-603D
	PS [bar]	41.5
	DN [φ]	<25
	PS*DN	-
	Category	0
Solenoid valve	Model	TEV-S1920DQ50
	PS [bar]	41.5
	DN [φ]	<25
	PS*DN	-
	Category	0
Stop valve(Liquid)	Model	-
	PS [bar]	41.5
	DN [φ]	<25
	PS*DN	-
	Category	0
Stop valve(Gas)	Model	-
	PS [bar]	41.5
	DN [φ]	<25
	PS*DN	-
	Category	0
Shutoff valve(Liquid)	Model	VPV-803DQ55
	PS [bar]	41.5
	DN [φ]	<25
	PS*DN	-
	Category	0
Shutoff valve(Gas)	Model	BPV-1706ADYQ101
	PS [bar]	41.5
	DN [φ]	<25
	PS*DN	-
	Category	0
Piping	Model	-
	PS [bar]	41.5
	DN [φ]	<25
	PS*DN	-
	Category	0

Document non contractuel. Mitsubishi Electric se réserve le droit d'opérer sans préavis, toutes modifications sur les données de ce document.

* La culture du meilleur