

Équipements sous pression

Annexe - Données détaillées

PUMY-P200YKM4

7 janvier 2026

No.	PUMY-P200YKM4	8 CV	
	Réfrigérant	R410A	
1	Compressor	Model	ANB52
		PS[bar]	41.5
		V[L]	4.2
		PS*V	174.3
2	Oil separator	PS[bar]	41.5
		V[L]	0.93
		PS*V	38.595
3	Accumulator	PS[bar]	23.0
		V[L]	7.55
		PS*V	173.65
4	High pressure switch	PS[bar]	41.5
		DN[φ]	21.7
		PS*DN	900.55
5	Heat exchanger	PS[bar]	41.5
		DN[φ]	7.94
		PS*DN	329.51
6	Solenoid valve	PS[bar]	41.5
		DN[φ]	7.94
		PS*DN	329.51
7	Linear expansion valve	PS[bar]	41.5
		DN[φ]	7.94
		PS*DN	329.51
8	4-way valve	PS[bar]	41.5
		DN[φ]	22.2
		PS*DN	921.3
9	valve(liquid)	PS[bar]	41.5
		DN[φ]	9.52
		PS*DN	395.08
10	valve(gas)	PS[bar]	41.5
		DN[φ]	19.05
		PS*DN	790.575
11	pipe(high pressure)	PS[bar]	41.5
		DN[φ]	19.05
		PS*DN	790.575
12	pipe(low pressure)	PS[bar]	23
		DN[φ]	19.05
		PS*DN	438.15

Document non contractuel. Mitsubishi Electric se réserve le droit d'opérer sans préavis, toutes modifications sur les données de ce document.

* La culture du meilleur