

HVAC System Calculator Results

Eu - PUAZ Series

Outdoor Unit: SUZ-M50VA2

Cooling Performance

6.70

SEER (Seasonal Energy Efficiency Ratio)

A++

5.5 kW

Heating Performance

4.10

SCOP (Seasonal Coefficient of Performance)

A+

4.3 kW

Annual Energy Consumption

285

kWh/year (Cooling)

1,458

kWh/year (Heating)

1,743

kWh/year (Total)

Sound Levels


64 dB(A)

Outdoor Unit

54 dB(A)


Indoor Unit


EU Energy Label




ENERG

енергия · ενεργεια






PLA-M50EA3/SUZ-M50VA2

SEER 


| | |
|------|-----|
| A+++ | A++ |
| A++ | |
| A+ | |
| A | |
| B | |
| C | |
| D | |


kW 5.5
 SEER 6.7
 kWh/annum 285


SCOP 

| | |
|------|----|
| A+++ | A+ |
| A++ | |
| A+ | |
| A | |
| B | |
| C | |
| D | |

| | | | |
|-----------|------|------|------|
| kW | 0.0 | 4.3 | 0.0 |
| SCOP | 0.0 | 4.1 | 0.0 |
| kWh/annum | 1458 | 1458 | 1458 |

 54dB

 64dB



ENERGIA · ЕНЕРГИЯ · ΕΝΕΡΓΕΙΑ · ENERGIA · ENERGY · ENERGIE · ENERGI

626/2011

Product Data Fiche

| | | | | | | | | |
|----------|-------------------------------------|-------------|--------------------------------|----------------|---------------------------------|-------------|-------------|--------|
| A | Model | C | Outdoor unit | SUZ-M50VA2 | | | | |
| | | B | Indoor unit 1 | PLA-M50EA3 | | | | |
| | | | Indoor unit 2 | - | | | | |
| | | | Indoor unit 3 | - | | | | |
| | | | Indoor unit 4 | - | | | | |
| | | | Indoor unit 5 | - | | | | |
| | | | Indoor unit 6 | - | | | | |
| D | Sound power level, indoors/outdoors | F | Outside | dB(A) | 64 | | | |
| | | E | Inside 1 | dB(A) | 54 | | | |
| | | | Inside 2 | dB(A) | - | | | |
| | | | Inside 3 | dB(A) | - | | | |
| | | | Inside 4 | dB(A) | - | | | |
| | | | Inside 5 | dB(A) | - | | | |
| | | | Inside 6 | dB(A) | - | | | |
| G | Refrigerant | R32 GWP 675 | | | | | | |
| H | Cooling | SEER | | | 6.70 | | | |
| | | J | Energy efficiency class | | A++ | | | |
| | | K | Annual energy consumption | kWh/annum | 285 | | | |
| | | L | Design load | kW | 5.5 | | | |
| | | | Warmer | Average | Colder | | | |
| M | Heating | SCOP | | | 0.00 | 4.10 | 0.00 | |
| | | J | Energy efficiency class | | × | A+ | × | |
| | | K | Annual electricity consumption | | - | 1458 | - | |
| | | L | Design load | | - | 4.3 | - | |
| | | N | Declared capacity | P | at reference design temperature | ×(×°C) | 3.8(-10°C) | ×(×°C) |
| | | | | R | at bivalent temperature | ×(×°C) | 3.8(-7°C) | ×(×°C) |

| | | | | | | | | |
|--|--|----------|--------------------------|----------|--------------------------------------|--------|------------|--------|
| | | | | S | at operation limit temperature | x(x°C) | 3.8(-10°C) | x(x°C) |
| | | T | Back up heating capacity | | | x | 0.5 | x |

| | | | | | | | |
|---|--|--|---|--|---|--|---|
| | Deutsch Français Nederlands Español | Italiano Ελληνικά Português | Svenska Česky Slovensky Magyar | Polski Slovensko Български Română | Eesti Gaeilge Latviski Türkçe Lietuvių k. | Malti Suomi Türkçe Hrvatski | Русский Norsk Українська |
| A | Modell Modèle Model Modelo | Modello Μοντέλο Modelo Modelo | Modell Model Model Model | Model Model Model Model | Model Dėbanamh Modelis Modelis | Mudell Malli Modelis Model | Модель Model Model Model |
| B | Innengerät Appareil intérieur Binnenunit Unidad interior | Unità interna Εσωτερική μονάδα Unidade interior Indendørsenhed | Inomhusenhet Vnitřní jednotka Vnitřní jednotka Belléri egység | Jednostka wewnętrzna Notranja enota Внутреннее ядро Unitate de interior | Siseseade Aonad laistigh Iekšējais ierīce Unitate de montuojamas įrenginys | Unità għal għewwa Sisäyksikkö İç ünite Unutarmaja jedinica | Внутренний прибор Innenårsenhet Внутришній блок |
| C | Außengerät Modèle extérieur Buitenunit Unidad exterior | Unità esterna Εξωτερική μονάδα Unidade exterior Utdendørsenhed | Utomhusenhet Vnější jednotka Vnější jednotka Kültéri egység | Jednostka zewnętrzna Zunanja enota Внешнее ядро Unitate de exterior | Välisseade Aonad lasmuigh Ārteļpas ierīce Lauke montuojamas įrenginys | Unità għal barra Ulkoyksikkö Diş ünite Vanjska jedinica | Наружный прибор Utdendørsenhet Зовнішній блок |
| D | Schalleistungspegel im Kühlmodus Niveaux de puissance corrects en mode de refroidissement Geluids niveaus in koelstand Niveles de potencia del sonido en el modo de refrigeración | Livelli di potenza sonora in modalità di raffreddamento Επίπεδα ισχύος ήχου στην κατάσταση ψύξης Níveis de potência sonora em modo de arrefecimento Lydystyrkeniveauer i kølefunktion | Bulleimivä i nedkylningsläget Úrovň hlukovosti v režimu chlazení Hladiny akustického výkonu v režime chladienia Hangnyomásszintek hűtés üzemmódban | Poziom mocy dźwięku w trybie chłodzenia Ravni zvočne moči v načinu hlajenja Нива на звуковата мощност в режим на охлаждане Nivel sonor în modul de răcire | Müratasemed jahutusrežiimis Leibhéal chumhachta faime ar mhodh fuairthe Akustiskās jaudas līmenis dzesēšanas režīmā Garso galios lygis vėsavimo režimu | Livelli tal-qawwa tal-hsejjes fil-modalità tat-tkessih Ānenvoimakkustastat viilen-nystlassa Soğutma modunda ses güç düzeyleri Razine zvučnog tlaka pri hlajenju | Значения уровня звуковой мощности в режиме охлаждения Lydtrykknivåer i avkjølingsmodus Рівні звукової потужності у режимі охолодження |
| E | Innen À l'intérieur Binnenkant Interior Interior | Interno Εσωτερικό Interior Indvendig | Interno Vnitř Vnitř Bent | Wewnętrzny Znotraj Вътре Interior | Sees Laistigh Iekšējās Vidinis | Sees Sisäpuoli İç taraf Unutra | Внутри Innenvidig Усередини |
| F | Außen À l'extérieur Buitenkant Exterior Exterior | Esterno Εξωτερικό Exterior Udvendig | Utsida Venku Venku A szababban | Zunaj Zunaj На открито Exterior | Väljas Lasmuigh Ārteļpā Išorinis | Barra Ulko puoli Diş taraf Vani | Снаружи Utvendig Назовні |

| | | | | | | | |
|---|---|---|---|--|--|--|--|
| | Deutsch Français Nederlands Español | Italiano Ελληνικά Português | Svenska Česky Slovensky Magyar | Polski Slovensko Български Română | Eesti Gaeilge Latviski Türkçe Lietuvių k. | Malti Suomi Türkçe Hrvatski | Русский Norsk Українська |
| G | Kühlmittel Réfrigérant Koelmiddel Refrigerante | Refrigerante Ψυκτικό Refrigerante Kølemiddel | Köldmedel Chladivo Chladivo Hűtőközeg | Czynnik chłodniczy Hladivo sredstvo Хладилен агент Refrigerent | Kūlmutusagens Cuisneán Aukstumagents Saldaus | Refrigerant Kylmäaine Soğutucu Rashladno sredstvo | Хладагент Kjølemiddel Холодагент |
| H | Kühlen Refroidissement Koelen Refrigeración | Raffreddamento Ψύξη Arrefecimento Køling | Kyla Chlazení Chlazenie Hűtés | Chłodzenie Hlajenje Охлаждане Răcire | Chłodzenie Fuarú Dzesēšana Vėsinimas | Jahutus Villennys Soğutma Hladjenje | Охлаждение Avkjøling Охлаждения |
| I | Energieeffizienzklasse Classe d'efficacité énergétique Energie-efficiëntieklasse Clase de eficiencia energética | Classe di efficienza energetica Κλάση ενεργειακής απόδοσης Classe de eficiența energetică | Energiklass Třída energetické účinnosti Trieda energetickej účinnosti | Klasa energetyczna Razred energetske učinkovitosti Клас на енергийна ефективност | Energiatehohususe klass Aicme éifeachtúlachta fuinnimh Energieeffektivitātes klase Enerģijas vartojimo efektyvumo klasė | Klassi tal-effiċjenza fl-użu tal-enerġija Energielehokkuusluokka Enerji verimlilik sınıfı Klasa energetске učinkovitosti | Клас ефективності використання енергії Energieeffektivitetsklasse Клас ефективності енергоспоживання |
| J | Jahresstromverbrauch *2 Consumption d'électricité annuelle *2 Jaarlijks elektriciteitsverbruik *2 Consumo anual de electricidad *2 | Consumo annuale di energia elettrica *2 Ετήσια κατανάλωση ρεύματος *2 Consumo anual de electricidade *2 Årligt elförbruk *2 | Årlig strömförbrukning *2 Roční spotřeba elektrické energie *2 Ročná spotřeba elektriny *2 Éves áramfogyasztás *2 | Zużycie prądu w skali roku *2 Letna poraba elektrike *2 Годишна консумация на електроенергия *2 Consum anual de electricitate *2 | Aastane voolutarbimus *2 Ídici leicreachais bhliantúil *2 Gada elektroenerģijas patēriņš *2 Metinis elektros energijos suvartojimas *2 | Konsum annwali tal-eletriku *2 Vuotäinen sähkönkulutus *2 Yllik elektrik tükemli *2 Yllik elektroenerģija *2 | Годовое потребление электроэнергии *2 Årlig strømförbruk *2 Річне споживання електроенергії *2 |
| K | Lastauslegung Charge de calcul Ontwerpbelasting Carga de diseño Heizen (Jahresdurchschnitt) | Carico nominale Σχεδιασμός φόρτισης Carga nominal Brugslast Riscaldamento (stagione media) | Dimensionerande belastning Jmenovitě zatížení Projektované zaťaženie Mértékezési terhelés Värme (genomsnittlig årstid) | Maksimalne obciążenie Nazivna obremenitev Проектен товар Sarcină nominală Ogrzewanie (średnie temperatury) | Maksymalne obciążenie Lõj deartha Aprékina slodze Projecktine apkrova Kütmine (keskmise hooaeg) | Projekteeritud koormus Limietu teho Tasarann yükü Težina uređaja Tishin (Stagun medju) | Расчетная нагрузка Uformingsbelastning Розрахунок навантаження Нагрев (средний сезон) Orpparming (ģenomsnittlig årstid) |
| L | Chauffage (moyenne saison) Verwarmen (gemiddeld seizoen) | Θέρμανση (Μέσο χρονικό διάστημα) Aquecimento (Média estação) | Topení (průměrná sezóna) Vykurovanie (Priemerná sezóna) | Ogrevanje (povprečni letni čas) Отопление (Среден сезон) | Téamh (meánséasúr) Silditšana (vidēj sezonā) | Lämmitys (vuodenajan keskiarvo) Istma (Ortalama mevsimlik) | Орpparming (ģenomsnittlig årstid) Опалення (у середній/теплий сезон) |
| M | Calefacción (temporada promedio) | Värme (genomsnittlig säsong) | Fűtés (átlagos időjárás) | Incălzire (sezon mediu) | Šildymas (vidutinio sezono) | Zagrijavanje (prosječna sezona) | Гарантированная мощность Ekiertet kapasitet Гарантована потужність |
| N | Nennkapazität Capacité déclarée Aangegeven capaciteit Capacitat declarada | Capacità dichiarata Δηλωμένη χωρητικότητα Capacitate declarada Erklæret kapasitet | Udåvnad kapacitet Deklarovaný výkon Névteljes teljesítmény | Deklarovaná pojemnosť Prijavljena zmogljivost Объявленная мощность Capacitate declarată w znamionowej temperaturze odniesienia | Deklararowana pojemność Toileadn fógartha Deklarirata jauda Capacitate declarată projekteerimise võrdlustemperatuurijuuress | Deklararad vörmsus Toileadn fógartha Declarirata kapasite Deklaruoclasis pajégumas Ftemperatura tad-disinn ta' referenza | Kapacitá dđikjarata limietu teho Bayan edilen kapasite Deklarirani kapacitet Ftemperatura tad-disinn ta' referenza |
| O | bei angegebener Referenztemperatur à la température de calcul de référence bij referentiewerptemperatuur a temperatura de diseño de referencia à bivalenter Temperatur à température bivalente bij bivalente temperatuur a temperatura bivalente | alla temperatura di progetto di riferimento σε θερμοκρασία σχεδιασμού αναφοράς à temperatura nominal de referencia ved brugsafhængig referencetemperatur alla temperatura bivalente σε θερμοκρασία διαθενοφύας λειτουργίας à temperatura bivalente ved bivalent temperatur | vid dimensionerande referenstemperatur při referenční výpočtové teplotě pri referenčnej výpočtovej teplote tervezési referenciáhozmérsékleten při bivalentní teplotě pri bivalentnej teplote bivalens hőmérsékleten | ob referenčni nazivni temperaturi pri izračunljivi projektni temperaturi ia temperatura de referință nominală w temperaturze bivalentnej při bivalentní temperaturi pri bivalentna temperatura ia temperatura de bivalentă | ag teocht deartha tagartha aprékina references temperaturūr esant norminei projektinei temperaturāi bivalentse temperatuurijuuress ag teocht dhéfhúsach bivalentā temperatūrā esant perējimo j dvejopo šildymo režimā temperatūrai | perumitoituasiämpötilassa referans tasarn sicačkliginda při referentnoj temperaturi ftemperatura bivalenti kaksiarvoisessa lämpötilassa iki deđerli sicačklika při bivalentnoj temperaturi | ved referansetemperatuur for utforming При эталонній розрахунковій температурі при бивалентной температуре ved bivalent temperatur При бивалентній температурі |
| P | bei Temperatur an der Betriebsgrenze à température de fonctionnement limite bij grens werkingstemperatuur a temperatura limite de funcionamiento | alla temperatura limite di funzionamento σε θερμοκρασία ορίου λειτουργίας à temperatura de limite de funcionamiento ved driftsgrænsetemperatur | vid driftstemperaturens gränsvärde při teplotě na hranici provozního limitu pri hraničnej prevádzkovej teplote maximális üzemi hőmérsékleten | w granicznej temperaturze roboczej při mejni delovni temperaturi ia temperatura limită de funcționare esant ribinei veikimo temperatūrai | tõotamise piirtemperatuurijuuress ag teocht teorann oibriüchän ia temperatura limită de funcționare esant ribinei veikimo temperatūrai | ftemperatura tal-limitu tat-ħaddim toimintarajalämpötilassa çalışma limiti sicačkliginda při granichnoj radnoj temperaturi | при предельной рабочей температуре ved temperatur for driftsgrense При граничной рабочей температурі |
| Q | Backup-Heizleistung Capacité de chauffage d'appoint Reserveverwarmingscapaciteit Capacidad de calefacción auxiliar | Capacità di riscaldamento addizionale Δυνατότητα εφεδρικής θέρμανσης Capacidade de aquecimento de reserva Reserveverwarmingscapaciteit | Kapacitet för reservvärme Kapacita záložního vytápění Výkon záložného vykurovacieho telesa Kisegítő fűtési teljesítmény | Zapozowa pojemność grzewcza Rezervna zmogljivost ogrevanja Мощност на спомогателно електрическо подгряване Capacitate de încălzire de siguranță | Tagavara küttevõimsus Toileadn téimh chúltaça Rezerves silditšaja jauda Pagalbinio šildymo pajégumas | Kapacitá tat-tishin ta' sostenn Varalämmitysteho Yedek ısıtma kapasitesi Capacitet rezervnog grįjanja | Резервная тепловая мощность Sikkerhetskapasitet for orpparming Резервна теплова потужність |

Product Information (*1)

| | |
|--------------------|--------------------|
| INDOOR MODEL 1/2/3 | PLA-M50EA3 / - / - |
| INDOOR MODEL 4/5/6 | - / - / - |
| OUTDOOR MODEL | SUZ-M50VA2 |

| Function (indicate if present) | | | |
|---|----------|-------|------|
| cooling | | | Y |
| heating | | | Y |
| Item | symbol | value | unit |
| Design load | | | |
| cooling | Pdesignc | 5.5 | kW |
| heating/Average | Pdesignh | 4.3 | kW |
| heating/Warmer | Pdesignh | × | kW |
| heating/Colder | Pdesignh | × | kW |
| Declared capacity for cooling, at indoor temperature 27(19)°C and outdoor temperature Tj | | | |
| Tj=35°C | Pdc | 5.50 | kW |
| Tj=30°C | Pdc | 4.00 | kW |
| Tj=25°C | Pdc | 2.60 | kW |
| Tj=20°C | Pdc | 1.20 | kW |
| Declared capacity for heating/Average season, at indoor temperature 20°C and outdoor temperature Tj | | | |
| Tj=-7°C | Pdh | 3.80 | kW |
| Tj=2°C | Pdh | 2.35 | kW |
| Tj=7°C | Pdh | 1.50 | kW |
| Tj=12°C | Pdh | 1.45 | kW |
| Tj=bivalent temperature | Pdh | 3.80 | kW |
| Tj=operating limit | Pdh | 3.80 | kW |
| Declared capacity for heating/Warmer season, at indoor temperature 20°C and outdoor temperature Tj | | | |
| Tj=2°C | Pdh | × | kW |
| Tj=7°C | Pdh | × | kW |
| Tj=12°C | Pdh | × | kW |
| Tj=bivalent temperature | Pdh | × | kW |
| Tj=operating limit | Pdh | × | kW |

| Declared capacity for heating/Colder season, at indoor temperature 20°C and outdoor temperature Tj | | | |
|---|----------|--------|----|
| Tj=-7°C | Pdh | × | kW |
| Tj=2°C | Pdh | × | kW |
| Tj=7°C | Pdh | × | kW |
| Tj=12°C | Pdh | × | kW |
| Tj=bivalent temperature | Pdh | × | kW |
| Tj=operating limit | Pdh | × | kW |
| Tj=-15°C | Pdh | × | kW |
| Bivalent temperature | | | |
| heating/Average | Tbiv | -7 | °C |
| heating/Warmer | Tbiv | × | °C |
| heating/Colder | Tbiv | × | °C |
| Operating limit temperature | | | |
| heating/Average | ToI | -10 | °C |
| heating/Warmer | ToI | × | °C |
| heating/Colder | ToI | × | °C |
| Cycling interval capacity | | | |
| for cooling | Pcycc | × | kW |
| for heating | Pcyh | × | kW |
| Degradation co-efficient cooling | Cdc | 0.25 | |
| Electric power input in power modes other than 'active mode' | | | |
| off mode | POFF | 8 | W |
| standby mode | PSB | 8 | W |
| thermostat - off mode | PTO(c/h) | 3 / 13 | W |
| crankcase heater mode | PCK | 0 | W |
| Capacity control (indicate one of three options) | | | |
| fixed | | N | |
| staged | | N | |
| variable | | Y | |

| If function includes heating: Indicate the heating season the information relates to. Include at least the heating season 'Average'. | | | |
|---|--------|-------|------|
| Average (mandatory) | | | Y |
| Warmer (if designated) | | | N |
| Colder (if designated) | | | N |
| Item | symbol | value | unit |

| Seasonal efficiency | | | |
|--|--------|-------|--|
| cooling | SEER | 6.7 | |
| heating/Average | SCOP/A | 4.1 | |
| heating/Warmer | SCOP/W | × | |
| heating/Colder | SCOP/C | × | |
| Declared energy efficiency ratio, at indoor temperature 27(19)°C and outdoor temperature Tj | | | |
| Tj=35°C | EERd | 3.40 | |
| Tj=30°C | EERd | 5.00 | |
| Tj=25°C | EERd | 8.00 | |
| Tj=20°C | EERd | 13.40 | |
| Declared coefficient of performance/Average season, at indoor temperature 20°C and outdoor temperature Tj | | | |
| Tj=-7°C | COPd | 2.50 | |
| Tj=2°C | COPd | 4.20 | |
| Tj=7°C | COPd | 5.20 | |
| Tj=12°C | COPd | 7.20 | |
| Tj=bivalent temperature | COPd | 2.50 | |
| Tj=operating limit | COPd | 2.00 | |
| Declared coefficient of performance/Warmer season, at indoor temperature 20°C and outdoor temperature Tj | | | |
| Tj=2°C | COPd | × | |
| Tj=7°C | COPd | × | |
| Tj=12°C | COPd | × | |
| Tj=bivalent temperature | COPd | × | |
| Tj=operating limit | COPd | × | |
| Declared coefficient of performance/Colder season, at indoor temperature 20°C and outdoor temperature Tj | | | |
| Tj=-7°C | COPd | × | |
| Tj=2°C | COPd | × | |
| Tj=7°C | COPd | × | |
| Tj=12°C | COPd | × | |
| Tj=bivalent temperature | COPd | × | |
| Tj=operating limit | COPd | × | |
| Tj=-15°C | COPd | × | |
| Cycling interval efficiency | | | |
| for cooling | EERcyc | × | |
| for heating | COPcyc | × | |
| Degradation co-efficient heating | Cdh | 0.25 | |

| Annual electricity consumption | | | |
|---|---|----------------|-------------------|
| cooling | QCE | 285 | kWh/a |
| heating/Average | QHE | 1458 | kWh/a |
| heating/Warmer | QHE | × | kWh/a |
| heating/Colder | QHE | × | kWh/a |
| Other items | | | |
| Sound power level (indoor model 1/2/3/4/5/6) | LWA | 54/0/0/0/0/0 | dB(A) |
| Sound power level (outdoor model) | LWA | 64 | dB(A) |
| Global warming potential | GWP (*2) | 675 | kgCO2eq. |
| Rated air flow (indoor model 1/2/3/4/5/6) | | 1080/-/-/-/-/- | m ³ /h |
| Rated air flow (outdoor model) | | 2748 | m ³ /h |
| Contact details for obtaining more information | MITSUBISHI ELECTRIC CORPORATION SHIZUOKA WORKS 3-18-1, Oshika, Suruga-ku, Shizuoka 422-8528, Japan E-mail: melshierp@MitsubishiElectric.co.jp | | |

(*1) This information is based on the "product information requirement" in COMMISSION REGULATION (EU) No206/2012.

(*2) This GWP value is based on Regulation(EU)No.517/2014 from IPCC 4th Assessment Report.

For Regulation (EU) No. 626/2011, which cites the IPCC Third Assessment Report, Climate Change 2001, the GWP is 550.

TECHNICAL DOCUMENTATION (1)

| | | | |
|---------------------------------|----------------|-----------------------|-----------------------|
| PACKAGED AIR CONDITIONER | INDOOR MODEL 1 | PLA-M50EA3 | H258 x W840 x D840 mm |
| | INDOOR MODEL 2 | - | |
| | INDOOR MODEL 3 | - | |
| | INDOOR MODEL 4 | - | |
| | INDOOR MODEL 5 | - | |
| | INDOOR MODEL 6 | - | |
| OUTDOOR MODEL | SUZ-M50VA2 | H714 x W800 x D285 mm | |

| Function | |
|-----------------|---|
| cooling | Y |
| heating | Y |


| The heating season | |
|---------------------------|---|
| Average (mandatory) | Y |
| Warmer (if designated) | N |
| Colder (if designated) | N |

| Capacity control | |
|-------------------------|---|
| fixed | N |
| staged | N |
| variable | Y |

| Item | symbol | value | unit |
|--------------------------------|--------|-------|------|
| Seasonal efficiency (2) | | | |
| cooling | SEER | 6.7 | |
| heating/Average | SCOP/A | 4.1 | |
| heating/Warmer | SCOP/W | × | |
| heating/Colder | SCOP/C | × | |

| Energy efficiency class | | | |
|--------------------------------|--------|------------|--|
| cooling | SEER | A++ | |
| heating/Average | SCOP/A | A+ | |
| heating/Warmer | SCOP/W | × | |
| heating/Colder | SCOP/C | × | |

| Other items | | | |
|--|--------------------|--------------|----------|
| Sound power level (indoor model 1/2/3/4/5/6) | LWA | 54/0/0/0/0/0 | dB(A) |
| Sound power level (outdoor model) | LWA | 64 | dB(A) |
| Refrigerant | | R32 | |
| Global warming potential | GWP ⁽³⁾ | 675 | kgCO2eq. |

| | |
|--|---|
| Identification and signature of the person empowered to bind the supplier |  Supplier Signature <hr/> Kunihiro Morishita Department Manager, Quality Assurance Department MITSUBISHI ELECTRIC CONSUMER PRODUCTS (THAILAND) CO.,LTD |
|--|---|

(¹) This information is based on COMMISSION DELEGATED REGULATION (EU) No626/2011.

(²) SEER/SCOP values are measured based on EN 14825:2016: Testing and rating at part load conditions and calculation of seasonal performance.

(³) This GWP value is based on Regulation(EU)No.517/2014 from IPCC 4th Assessment Report. For Regulation (EU) No. 626/2011, which cites the IPCC Third Assessment Report, Climate Change 2001, the GWP is 550.