



- HC HYDRAULIC CONNECTIONS
- SV SAFETY VALVE DISCHARGE
- IP POWER SUPPLY INLET
- AIR INLET
- AIR OUTLET
- MINIMUM CLEARANCE
- CENTER OF GRAVITY



Model	A [mm]	B [mm]	C [mm]	D [mm]	E [mm]	F [mm]	W1 [kg]	W2 [kg]	W3 [kg]	W4 [kg]	Weight without pump [kg]	Weight with pump [kg]	Center of gravity [mm]			G [mm]	H [mm]	L [mm]	M [mm]	HC Ø
MEHP-iB-G07 27Y	1453	1700	554	1507	497	1475	92	30	104	34	256	260	1345	265	850	112	565	1055	913	1" 1/4
MEHP-iB-G07 35Y	1453	1700	554	1507	497	1475	101	32	111	36	274	280	1345	265	850	112	565	1055	913	1" 1/2
MEHP-iB-G07 40Y	1703	1700	654	1757	597	1725	112	36	127	40	309	315	1595	265	850	112	565	1055	905	1" 1/2

01	AGGIUNTO PESO SENZA POMPA										16/05/2023		H. Shah				
REV. N°		DESCRIPTION										DATE		DRAWN			
DESCRIPTION: MEHP-iB 27Y..40Y G07												MITSUBISHI ELECTRIC HYDRONICS & IT COOLING SYSTEMS S.p.A.					
-																	
DESIGNER: H. Shah				CHECKER: M. Scarpa				APPROVER: F. Carletto				DATE: 05/01/2023		DRAWING N°:		REV.N°:	
SHEET: 1		Scale		Size						(xxx) QUOTE TO CHECK DURING PRODUCTION		CONFIDENTIAL DOCUMENT PROPERTY OF MEHITS SPA IT CANNOT BE REPRODUCED NOR DELIVERED WITHOUT COMPANY WRITTEN CONSENT					
OF: 1		1:10		A3								D4T9275001					
												01					