

7. ELECTRICAL CHARACTERISTICS

Ceiling concealed (Low noise/Low static pressure type)

Symbols: MCA (Max.Circuit Amps =1.25xFLA), FLA (Full Load Amps)
IFM (Indoor Fan Motor), Output (Fan motor rated output)

PEFY-P-VMR-E-L/R	Power supply			IFM	
	Volts/Hz	Range +-10%	MCA(A) (50/60Hz)	Output (kW)	FLA(A) (50/60Hz)
PEFY-P20VMR-E-L/R	220-240V/50Hz 220-230V/60Hz	Max.: 264V Min.: 198V	0.37/0.37	0.018	0.29/0.29
PEFY-P25VMR-E-L/R			0.37/0.37	0.018	0.29/0.29
PEFY-P32VMR-E-L/R			0.43/0.48	0.023	0.34/0.38

PEFY-P-VMS1-E	Power supply			IFM	
	Volts/Hz	Range +-10%	MCA(A) (50/60Hz)	Output (kW)	FLA(A) (50/60Hz)
PEFY-P15VMS1-E	220-240V/50Hz 220-240V/60Hz	Max.: 264V Min.: 198V	0.63/0.63	0.096	0.50/0.50
PEFY-P20VMS1-E			0.70/0.70	0.096	0.56/0.56
PEFY-P25VMS1-E			0.75/0.75	0.096	0.60/0.60
PEFY-P32VMS1-E			0.75/0.75	0.096	0.60/0.60
PEFY-P40VMS1-E			0.83/0.82	0.096	0.66/0.65
PEFY-P50VMS1-E			1.02/1.00	0.096	0.81/0.80
PEFY-P63VMS1-E			1.08/1.07	0.096	0.86/0.85

PEFY-P-VMS1L-E	Power supply			IFM	
	Volts/Hz	Range +-10%	MCA(A) (50/60Hz)	Output (kW)	FLA(A) (50/60Hz)
PEFY-P15VMS1L-E	220-240V/50Hz 220-240V/60Hz	Max.: 264V Min.: 198V	0.46/0.46	0.096	0.37/0.37
PEFY-P20VMS1L-E			0.54/0.54	0.096	0.43/0.43
PEFY-P25VMS1L-E			0.59/0.59	0.096	0.47/0.47
PEFY-P32VMS1L-E			0.59/0.59	0.096	0.47/0.47
PEFY-P40VMS1L-E			0.68/0.68	0.096	0.54/0.54
PEFY-P50VMS1L-E			0.84/0.84	0.096	0.67/0.67
PEFY-P63VMS1L-E			0.91/0.91	0.096	0.73/0.73

PEFY-P-VMR-E-L/R, VMS1(L)-E