

8. ELECTRICAL CHARACTERISTICS

Floor standing (Exposed 2-way/Exposed/Concealed type)

Symbols: MCA (Max.Circuit Amps =1.25xFLA), FLA (Full Load Amps)
IFM (Indoor Fan Motor), Output (Fan motor rated output)

PFFY-P-VKM-E2	Power supply			IFM	
	Volts/Hz	Range +-10%	MCA(A)	Output (kW)	FLA(A)
PFFY-P20VKM-E2	220-240V/50Hz	Max.: 264V Min.: 198V	0.25	0.03x2	0.20
PFFY-P25VKM-E2			0.25	0.03x2	0.20
PFFY-P32VKM-E2			0.25	0.03x2	0.20
PFFY-P40VKM-E2			0.30	0.03x2	0.24

PFFY-P-VLEM-E	Power supply			IFM	
	Volts/Hz	Range +-10%	MCA(A) (50/60Hz)	Output (kW)	FLA(A) (50/60Hz)
PFFY-P20VLEM-E	220-240V/50Hz 208-230V/60Hz	Max.: 264V Min.: 187V	0.24/0.31	0.015	0.19/0.25
PFFY-P25VLEM-E			0.24/0.31	0.015	0.19/0.25
PFFY-P32VLEM-E			0.36/0.38	0.018	0.29/0.30
PFFY-P40VLEM-E			0.40/0.41	0.030	0.32/0.33
PFFY-P50VLEM-E			0.50/0.51	0.035	0.40/0.41
PFFY-P63VLEM-E			0.58/0.59	0.050	0.46/0.47

PFFY-P-VLRM-E	Power supply			IFM	
	Volts/Hz	Range +-10%	MCA(A) (50/60Hz)	Output (kW)	FLA(A) (50/60Hz)
PFFY-P20VLRM-E	220-240V/50Hz 208-230V/60Hz	Max.: 264V Min.: 187V	0.24/0.31	0.015	0.19/0.25
PFFY-P25VLRM-E			0.24/0.31	0.015	0.19/0.25
PFFY-P32VLRM-E			0.36/0.38	0.018	0.29/0.30
PFFY-P40VLRM-E			0.40/0.41	0.030	0.32/0.33
PFFY-P50VLRM-E			0.50/0.51	0.035	0.40/0.41
PFFY-P63VLRM-E			0.58/0.59	0.050	0.46/0.47

PFFY-P-VLRMM-E	Power supply			IFM	
	Volts/Hz	Range +-10%	MCA(A) (50/60Hz)	Output (kW)	FLA(A) (50/60Hz)
PFFY-P20VLRMM-E	220-240V/50Hz 220-240V/60Hz	Max.: 264V Min.: 198V	0.59/0.58	0.096	0.47/0.46
PFFY-P25VLRMM-E			0.59/0.58	0.096	0.47/0.46
PFFY-P32VLRMM-E			0.69/0.69	0.096	0.55/0.55
PFFY-P40VLRMM-E			0.78/0.76	0.096	0.62/0.61
PFFY-P50VLRMM-E			0.80/0.79	0.096	0.64/0.63
PFFY-P63VLRMM-E			0.93/0.93	0.096	0.74/0.74

PFFY-P-VKM-E2, VLEM-E, VLRM-E, VLRMM-E