

9. ELECTRICAL CHARACTERISTICS

Ceiling cassette (2-way flow type)

Symbols: MCA (Max.Circuit Amps =1.25xFLA), FLA (Full Load Amps)
IFM (Indoor Fan Motor), Output (Fan motor rated output)

PLFY-P-VLMD-E	Power supply			IFM	
	Volts/Hz	Range +-10%	MCA(A) (50/60Hz)	Output (kW)	FLA(A) (50/60Hz)
PLFY-P20VLMD-E	220-240V/50Hz 220-230V/60Hz	Max.: 264V Min.: 198V	0.45/0.46	0.015	0.36/0.37
PLFY-P25VLMD-E			0.45/0.46	0.015	0.36/0.37
PLFY-P32VLMD-E			0.45/0.46	0.015	0.36/0.37
PLFY-P40VLMD-E			0.50/0.53	0.015	0.40/0.42
PLFY-P50VLMD-E			0.51/0.54	0.020	0.41/0.43
PLFY-P63VLMD-E			0.61/0.64	0.020	0.49/0.51
PLFY-P80VLMD-E			0.90/0.93	0.020	0.72/0.74
PLFY-P100VLMD-E			0.94/1.10	0.030	0.75/0.88
PLFY-P125VLMD-E			1.69/1.69	0.078x2	1.35/1.35

PLFY-P-VLMD-E