

EQUIPEMENT SOUS PRESSION

ANNEXE - DONNÉES DÉTAILLÉES

MXZ-3F54/68VF4.

No			MXZ-3F54VF4-E1	MXZ-3F68VF4-E1
1	Compressor	Model	SVB130FBBM1T	SVB172FCKM1T
		PS[bar]	41,5	41,5
		V[L]	1	1
		PS*V	41,5	41,5
2	Oil separator	PS[bar]	41,5	41,5
		V[L]	0,374	0,374
		PS*V	15,5	15,5
3	Muffler	PS[bar]	41,5	41,5
		V[L]	0,05	0,05
		PS*V	2,1	2,1
4	High pressure switch	PS[bar]	45	45
		DN[φ]	20	20
		PS*DN	900	900
5	Check valve	PS[bar]	-	-
		DN[φ]	-	-
		PS*DN	-	-
6	Reversing valve	PS[bar]	41,5	41,5
		DN[φ]	35	35
		PS*DN	1453	1453
7	Header	PS[bar]	41,5	41,5
		DN[φ]	<25	<25
		PS*DN	-	-
8	Heat exchanger	PS[bar]	41,5	41,5
		DN[φ]	<25	<25
		PS*DN	-	-
9	Distributor	PS[bar]	41,5	41,5
		DN[φ]	<25	<25
		PS*DN	-	-
10	LEV	PS[bar]	41,5	41,5
		DN[φ]	<25	<25
		PS*DN	-	-
11	(Accumulator)	PS[bar]	41,5	41,5
		V[L]	1,9	1,9
		PS*V	77	77
12	Stop valve (Liquid)	PS[bar]	41,5	41,5
		DN[φ]	<25	<25
		PS*DN	-	-
13	Ball valve (Gas)	PS[bar]	-	-
		DN[φ]	-	-
		PS*DN	-	-
14	Check valve (Low side)	PS[bar]	-	-
		DN[φ]	-	-
		PS*DN	-	-
15	Low pressure switch	PS[bar]	-	-
		DN[φ]	-	-
		PS*DN	-	-
16	Pipes	PS[bar]	41,5	41,5
		DN[φ]	<25	<25
		PS*DN	-	-
17	Stop valve (Gas)	PS[bar]	41,5	41,5
		DN[φ]	<25	<25
		PS*DN	-	-

* La culture du meilleur