

This information was generated by the HP KEYMARK database on 25 Feb 2023

	Ecodan Eco Inverter 6/8/10H+200D	Reg. No.	037-0089-22
Certificate Holder	Mitsubishi Electric Air Conditioning Systems Europe LTD		
	Nettlehill Road, Houston Industrial Estate		EH54 5EQ
	Livingston		United Kingdom
Certification Body	SZU - Strojirensky zkusebni ustav (Engineering Test Institute, Public Enterprise)		
Subtype title	Ecodan Eco Inverter 6/8/10H+200D		
Heat Pump Type	Outdoor Air/Water		
Refrigerant	R32		
Mass of Refrigerant	1.1 kg		
Certification Date	02.11.2022		
Testing basis	HP Keymark scheme rules rev. no. 9		

Model: SUZ-SHWM60VAH + ERST20D-*M*D

Configure model	
Model name	SUZ-SHWM60VAH + ERST20D-*M*D
Application	Heating + DHW + low temp
Units	Indoor + Outdoor
Climate Zone	n/a
Reversibility	Yes
Cooling mode application (optional)	n/a

General Data	
Power supply	1x230V 50Hz

Heating

EN 14511-2		
	Low temperature	Medium temperature
Heat output	5 kW	5 kW
El input	1.01 kW	1.7 kW
COP	4.95	2.94

EN 14511-4	
Shutting off the heat transfer medium flow	passed
Complete power supply failure	passed
Defrost test	passed
Starting and operating test	passed

Average Climate

This information was generated by the HP KEYMARK database on 25 Feb 2023

EN 12102-1

	Low temperature	Medium temperature
Sound power level indoor	41 dB(A)	41 dB(A)
Sound power level outdoor	57 dB(A)	57 dB(A)

EN 14825

	Low temperature	Medium temperature
η_s	178 %	128 %
Prated	6.1 kW	6 kW
SCOP	4.53	3.27
Tbiv	-10 °C	-7 °C
TOL	-25 °C	-25 °C
Pdh Tj = -7°C	5.4 kW	5.31 kW
COP Tj = -7°C	2.78	1.85
Cdh Tj = -7 °C	0.992	0.995
Pdh Tj = +2°C	4.1 kW	3.7 kW
COP Tj = +2°C	4.43	3.13
Cdh Tj = +2 °C	0.984	0.987
Pdh Tj = +7°C	3.4 kW	3.1 kW
COP Tj = +7°C	6.27	4.66
Cdh Tj = +7 °C	0.972	0.977

This information was generated by the HP KEYMARK database on 25 Feb 2023

Pdh Tj = 12°C	3.7 kW	3.9 kW
COP Tj = 12°C	7.11	6.53
Cdh Tj = +12 °C	0.971	0.975
Pdh Tj = Tbiv	6.1 kW	5.31 kW
COP Tj = Tbiv	2.26	1.85
Pdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	6.1 kW	5.8 kW
COP Tj = TOL or COP Tj = Tdesignh if TOL < Tdesignh	2.26	1.64
Cdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	0.994	0.996
WTOL	60 °C	60 °C
Poff	15 W	15 W
PTO	15 W	15 W
PSB	15 W	15 W
PCK	0 W	0 W
Supplementary Heater: Type of energy input	Electricity	Electricity
Supplementary Heater: PSUP	0 kW	0.2 kW
Annual energy consumption Qhe	2783 kWh	3794 kWh

Domestic Hot Water (DHW)

Average Climate

This information was generated by the HP KEYMARK database on 25 Feb 2023

EN 16147	
Declared load profile	L
Efficiency η_{DHW}	144 %
COP	3.5
Heating up time	1:49 h:min
Standby power input	25 W
Reference hot water temperature	51.5 °C
Mixed water at 40°C	274 l

Model: SUZ-SHWM60VAH + ERSD-*M*D

Configure model	
Model name	SUZ-SHWM60VAH + ERSD-*M*D
Application	Heating (medium temp)
Units	Indoor + Outdoor
Climate Zone	n/a
Reversibility	Yes
Cooling mode application (optional)	n/a

General Data	
Power supply	1x230V 50Hz

Heating

EN 14511-2		
	Low temperature	Medium temperature
Heat output	5 kW	5 kW
El input	1.01 kW	1.7 kW
COP	4.95	2.94

EN 14511-4	
Shutting off the heat transfer medium flow	passed
Complete power supply failure	passed
Defrost test	passed
Starting and operating test	passed

Average Climate

This information was generated by the HP KEYMARK database on 25 Feb 2023

EN 12102-1

	Low temperature	Medium temperature
Sound power level indoor	41 dB(A)	41 dB(A)
Sound power level outdoor	57 dB(A)	57 dB(A)

EN 14825

	Low temperature	Medium temperature
η_s	178 %	128 %
Prated	6.1 kW	6 kW
SCOP	4.53	3.27
Tbiv	-10 °C	-7 °C
TOL	-25 °C	-25 °C
Pdh Tj = -7°C	5.4 kW	5.31 kW
COP Tj = -7°C	2.78	1.85
Cdh Tj = -7 °C	0.992	0.995
Pdh Tj = +2°C	4.1 kW	3.7 kW
COP Tj = +2°C	4.43	3.13
Cdh Tj = +2 °C	0.984	0.987
Pdh Tj = +7°C	3.4 kW	3.1 kW
COP Tj = +7°C	6.27	4.66
Cdh Tj = +7 °C	0.972	0.977

This information was generated by the HP KEYMARK database on 25 Feb 2023

Pdh Tj = 12°C	3.7 kW	3.9 kW
COP Tj = 12°C	7.11	6.53
Cdh Tj = +12 °C	0.971	0.975
Pdh Tj = Tbiv	6.1 kW	5.31 kW
COP Tj = Tbiv	2.26	1.85
Pdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	6.1 kW	5.8 kW
COP Tj = TOL or COP Tj = Tdesignh if TOL < Tdesignh	2.26	1.64
Cdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	0.994	0.996
WTOL	60 °C	60 °C
Poff	15 W	15 W
PTO	15 W	15 W
PSB	15 W	15 W
PCK	0 W	0 W
Supplementary Heater: Type of energy input	Electricity	Electricity
Supplementary Heater: PSUP	0 kW	0.2 kW
Annual energy consumption Qhe	2783 kWh	3794 kWh

Model: SUZ-SWM80VA2 + ERST20D-*M*D

Configure model

Model name	SUZ-SWM80VA2 + ERST20D-*M*D
Application	Heating + DHW + low temp
Units	Indoor + Outdoor
Climate Zone	n/a
Reversibility	Yes
Cooling mode application (optional)	n/a

General Data

Power supply	1x230V 50Hz
--------------	-------------

Heating

EN 14511-2

	Low temperature	Medium temperature
Heat output	6 kW	6 kW
El input	1.18 kW	2 kW
COP	5.1	3

EN 14511-4

Shutting off the heat transfer medium flow	passed
Complete power supply failure	passed
Defrost test	passed
Starting and operating test	passed

Average Climate

This information was generated by the HP KEYMARK database on 25 Feb 2023

EN 12102-1

	Low temperature	Medium temperature
Sound power level indoor	41 dB(A)	41 dB(A)
Sound power level outdoor	59 dB(A)	59 dB(A)

EN 14825

	Low temperature	Medium temperature
η_s	187 %	135 %
Prated	6.6 kW	7 kW
SCOP	4.74	3.44
Tbiv	-10 °C	-7 °C
TOL	-25 °C	-25 °C
Pdh Tj = -7°C	5.9 kW	6.2 kW
COP Tj = -7°C	3.16	1.91
Cdh Tj = -7 °C	0.992	0.995
Pdh Tj = +2°C	4.4 kW	3.8 kW
COP Tj = +2°C	4.61	3.39
Cdh Tj = +2 °C	0.984	0.987
Pdh Tj = +7°C	3.4 kW	3.1 kW
COP Tj = +7°C	6.22	4.69
Cdh Tj = +7 °C	0.973	0.977

This information was generated by the HP KEYMARK database on 25 Feb 2023

Pdh Tj = 12°C	3.7 kW	3.9 kW
COP Tj = 12°C	7.38	6.67
Cdh Tj = +12 °C	0.97	0.974
Pdh Tj = Tbiv	6.6 kW	6.2 kW
COP Tj = Tbiv	2.4	1.91
Pdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	6.6 kW	5.8 kW
COP Tj = TOL or COP Tj = Tdesignh if TOL < Tdesignh	2.4	1.68
Cdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	0.995	0.996
WTOL	60 °C	60 °C
Poff	15 W	15 W
PTO	15 W	15 W
PSB	15 W	15 W
PCK	0 W	0 W
Supplementary Heater: Type of energy input	Electricity	Electricity
Supplementary Heater: PSUP	0 kW	1.2 kW
Annual energy consumption Qhe	2874 kWh	4207 kWh

Domestic Hot Water (DHW)

Average Climate

This information was generated by the HP KEYMARK database on 25 Feb 2023

EN 16147	
Declared load profile	L
Efficiency η_{DHW}	144 %
COP	3.5
Heating up time	1:49 h:min
Standby power input	25 W
Reference hot water temperature	51.5 °C
Mixed water at 40°C	274 l

Model: SUZ-SWM80VA2 + ERSD-*M*D

Configure model	
Model name	SUZ-SWM80VA2 + ERSD-*M*D
Application	Heating (medium temp)
Units	Indoor + Outdoor
Climate Zone	n/a
Reversibility	Yes
Cooling mode application (optional)	n/a

General Data	
Power supply	1x230V 50Hz

Heating

EN 14511-2		
	Low temperature	Medium temperature
Heat output	6 kW	6 kW
El input	1.18 kW	2 kW
COP	5.1	3

EN 14511-4	
Shutting off the heat transfer medium flow	passed
Complete power supply failure	passed
Defrost test	passed
Starting and operating test	passed

Average Climate

This information was generated by the HP KEYMARK database on 25 Feb 2023

EN 12102-1

	Low temperature	Medium temperature
Sound power level indoor	41 dB(A)	41 dB(A)
Sound power level outdoor	59 dB(A)	59 dB(A)

EN 14825

	Low temperature	Medium temperature
η_s	187 %	135 %
Prated	6.6 kW	7 kW
SCOP	4.74	3.44
Tbiv	-10 °C	-7 °C
TOL	-25 °C	-25 °C
Pdh Tj = -7°C	5.9 kW	6.2 kW
COP Tj = -7°C	3.16	1.91
Cdh Tj = -7 °C	0.992	0.995
Pdh Tj = +2°C	4.4 kW	3.8 kW
COP Tj = +2°C	4.61	3.39
Cdh Tj = +2 °C	0.984	0.987
Pdh Tj = +7°C	3.4 kW	3.1 kW
COP Tj = +7°C	6.22	4.69
Cdh Tj = +7 °C	0.973	0.977

This information was generated by the HP KEYMARK database on 25 Feb 2023

Pdh Tj = 12°C	3.7 kW	3.9 kW
COP Tj = 12°C	7.38	6.67
Cdh Tj = +12 °C	0.97	0.974
Pdh Tj = Tbiv	6.6 kW	6.2 kW
COP Tj = Tbiv	2.4	1.91
Pdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	6.6 kW	5.8 kW
COP Tj = TOL or COP Tj = Tdesignh if TOL < Tdesignh	2.4	1.68
Cdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	0.995	0.996
WTOL	60 °C	60 °C
Poff	15 W	15 W
PTO	15 W	15 W
PSB	15 W	15 W
PCK	0 W	0 W
Supplementary Heater: Type of energy input	Electricity	Electricity
Supplementary Heater: PSUP	0 kW	1.2 kW
Annual energy consumption Qhe	2874 kWh	4207 kWh

Model: SUZ-SWM100VA + ERST20D-*M*D

Configure model

Model name	SUZ-SWM100VA + ERST20D-*M*D
Application	Heating + DHW + low temp
Units	Indoor + Outdoor
Climate Zone	n/a
Reversibility	Yes
Cooling mode application (optional)	n/a

General Data

Power supply	1x230V 50Hz
--------------	-------------

Heating

EN 14511-2

	Low temperature	Medium temperature
Heat output	7.5 kW	7.5 kW
El input	1.55 kW	2.68 kW
COP	4.85	2.8

EN 14511-4

Shutting off the heat transfer medium flow	passed
Complete power supply failure	passed
Defrost test	passed
Starting and operating test	passed

Average Climate

This information was generated by the HP KEYMARK database on 25 Feb 2023

EN 12102-1

	Low temperature	Medium temperature
Sound power level indoor	41 dB(A)	41 dB(A)
Sound power level outdoor	60 dB(A)	60 dB(A)

EN 14825

	Low temperature	Medium temperature
η_s	182 %	134 %
Prated	7.8 kW	7.5 kW
SCOP	4.61	3.43
Tbiv	-10 °C	-7 °C
TOL	-25 °C	-25 °C
Pdh Tj = -7°C	6.9 kW	6.63 kW
COP Tj = -7°C	2.99	1.8
Cdh Tj = -7 °C	0.993	0.996
Pdh Tj = +2°C	4.5 kW	4.1 kW
COP Tj = +2°C	4.57	3.41
Cdh Tj = +2 °C	0.985	0.988
Pdh Tj = +7°C	3.4 kW	3.5 kW
COP Tj = +7°C	5.84	4.79
Cdh Tj = +7 °C	0.974	0.979

This information was generated by the HP KEYMARK database on 25 Feb 2023

Pdh Tj = 12°C	3.7 kW	3.9 kW
COP Tj = 12°C	6.98	6.9
Cdh Tj = +12 °C	0.972	0.973
Pdh Tj = Tbiv	7.8 kW	6.63 kW
COP Tj = Tbiv	2.34	1.8
Pdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	7.8 kW	6.1 kW
COP Tj = TOL or COP Tj = Tdesignh if TOL < Tdesignh	2.34	1.69
Cdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	0.995	0.996
WTOL	60 °C	60 °C
Poff	15 W	15 W
PTO	15 W	15 W
PSB	15 W	15 W
PCK	0 W	0 W
Supplementary Heater: Type of energy input	Electricity	Electricity
Supplementary Heater: PSUP	0 kW	1.4 kW
Annual energy consumption Qhe	3492 kWh	4512 kWh

Domestic Hot Water (DHW)

Average Climate

This information was generated by the HP KEYMARK database on 25 Feb 2023

EN 16147	
Declared load profile	L
Efficiency η_{DHW}	144 %
COP	3.5
Heating up time	1:49 h:min
Standby power input	25 W
Reference hot water temperature	51.5 °C
Mixed water at 40°C	274 l

Model: SUZ-SWM100VA + ERSD-*M*D

Configure model	
Model name	SUZ-SWM100VA + ERSD-*M*D
Application	Heating (medium temp)
Units	Indoor + Outdoor
Climate Zone	n/a
Reversibility	Yes
Cooling mode application (optional)	n/a

General Data	
Power supply	1x230V 50Hz

Heating

EN 14511-2		
	Low temperature	Medium temperature
Heat output	7.5 kW	7.5 kW
El input	1.55 kW	2.68 kW
COP	4.85	2.8

EN 14511-4	
Shutting off the heat transfer medium flow	passed
Complete power supply failure	passed
Defrost test	passed
Starting and operating test	passed

Average Climate

This information was generated by the HP KEYMARK database on 25 Feb 2023

EN 12102-1

	Low temperature	Medium temperature
Sound power level indoor	41 dB(A)	41 dB(A)
Sound power level outdoor	60 dB(A)	60 dB(A)

EN 14825

	Low temperature	Medium temperature
η_s	182 %	134 %
Prated	7.8 kW	7.5 kW
SCOP	4.61	3.43
Tbiv	-10 °C	-7 °C
TOL	-25 °C	-25 °C
Pdh Tj = -7°C	6.9 kW	6.63 kW
COP Tj = -7°C	2.99	1.8
Cdh Tj = -7 °C	0.993	0.996
Pdh Tj = +2°C	4.5 kW	4.1 kW
COP Tj = +2°C	4.57	3.41
Cdh Tj = +2 °C	0.985	0.988
Pdh Tj = +7°C	3.4 kW	3.5 kW
COP Tj = +7°C	5.84	4.79
Cdh Tj = +7 °C	0.974	0.979

This information was generated by the HP KEYMARK database on 25 Feb 2023

Pdh Tj = 12°C	3.7 kW	3.9 kW
COP Tj = 12°C	6.98	6.9
Cdh Tj = +12 °C	0.972	0.973
Pdh Tj = Tbiv	7.8 kW	6.63 kW
COP Tj = Tbiv	2.34	1.8
Pdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	7.8 kW	6.1 kW
COP Tj = TOL or COP Tj = Tdesignh if TOL < Tdesignh	2.34	1.69
Cdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	0.995	0.996
WTOL	60 °C	60 °C
Poff	15 W	15 W
PTO	15 W	15 W
PSB	15 W	15 W
PCK	0 W	0 W
Supplementary Heater: Type of energy input	Electricity	Electricity
Supplementary Heater: PSUP	0 kW	1.4 kW
Annual energy consumption Qhe	3492 kWh	4512 kWh